Holyhead Marine

holyheadmarine.co.uk

Offshore Raiding Craft Forward Console Variant

MAIN SPECIFICATION

Length OA (inc fender) **Beam OA (inc fender) Draft Light / Loaded Displacement Light / Loaded Speed Light / Loaded** Range Turning Acceleration Stopping Engines

Gearboxes Propulsion

9.1m 2.9m 0.56m / 0.66m 4200 kg inc fuel & 2 crew / 5900 kg 40 knots / 32 knots In excess of 200nm 1.5 boat lengths at max speed 0 - 30 Knts in 10 seconds 1.5 boat lengths from max speed Twin Steyr M0256K43 high speed diesel engines each developing 250Hp/184Kw at 4300rpm ZF63 reduction gearbox (1.514:1) **Twin Rolls Royce (Kamewa) FF270 Waterjets** Fabricated Aluminium (Grade 5083)



Hull

CAPACITIES

Main Fuel Tank Reserve Fuel Tank Total Payload capacity 635 Litres

85 Litres

Combination of troops, equipment and weapons up to 1700kg

AUXILIARY EQUIPMENT

Communications - Marine VHF. Navigation - Chart plotter with DGPS Electrical - 24V DC, Insulated return

SPECIAL FEATURES

Including:

Foward console position to provide aft loading area

Optional Dyneema ballistic protection to defeat 7.62mm x 39 Ball at 20m

Elastomer covered closed cell PU foam fender

Air transportable in C130 J MK IV or under-slung Chinook CH47 and Merlin Helicopters

Removable seating and fairings for ease of transportation and flexibility of function

Optional road trailer conforming to EU regulations

Infrared and visible convoy lights

Infrared flood light

Optional Equipment

Shipping cradle

Radar reflector

Intercom system

Boat cover

Launching trolley

Military Communications systems

Boat trailer

Night vision camera system

HD radar system

CLASSIFICATION

Built in accordance with MCA SCV – Code of Practice, Structure designed and surveyed to LRS SSC rules









Holyhead Marine Services Limited Newry Beach Yard, Holyhead, Anglesey, LL65 1YB, Wales, UK

Tel: +44(0)1407 760111 Fax: +44(0)1407 764531 e-mail: marine.services@holyhead.co.uk

website: www.holyhead.co.uk

Registered in London 895484



